


## 740

R 20-25



Curve dima 5D 90° da tubo senza saldatura  
 Seamless elbow 5D 90°  
 Nahtlose Rohrbögen BA5 90°  
 Courbe à souder 5D 90° tiré de tube acier sans soudure  
 Curva para soldar 5D 90° (de tubo sin soldatura)

Norma: EN 10253-1 (DIN 2605)  
 Materiale: R. St. 37.0.S

Codice Code	DN	DN inch	DN mm	S mm	R mm	B mm	kg		Prezzo Price €
740213000	15	1/2"	21,3	2	42,5	53	0,08	50	3,195
740269000	20	3/4"	26,9	2,3	57,5	71	0,13	40	3,195
740337000	25	1"	33,7	2,6	72,5	89	0,2	30	3,490
740424000	32	1" 1/4	42,4	2,6	92,5	114	0,37	20	3,945
740483000	40	1" 1/2	48,3	2,6	107,5	132	0,5	25	4,880
740603000	50	2"	60,3	2,9	135	165	0,89	15	7,220
740761000	65	2" 1/2	76,1	2,9	175	213	1,44	5	9,890
740889000	80	3"	88,9	3,2	205	250	2,22	5	14,420
740101000	-	3" 1/2	101,6	3,6	235	286	3,21	4	29,625
740108000	-	-	108	3,6	253	307	3,68	4	29,565
740114000	100	4"	114,3	3,6	270	327	4,17	4	26,440
740133000	-	-	133	4	311,5	378	6,23	3	90,390
740139000	125	5"	139,7	4	330	400	6,94	3	95,400
740159000	-	-	159	4,5	375	454	10,1	2	122,665
740168000	150	6"	168,3	4,5	390	474	11,14	2	123,270
740219000	200	8"	219,1	6,3	510	620	26,75	2	283,650
740273000	250	10"	273	6,3	650	787	42,8	1	570,060
740323000	300	12"	323,9	7,1	775	937	70	1	912,800

### Tolleranze dimensionali / Dimensional tolerances

D = ± 1% D MIN ± 0,5 mm

S = S ≤ 4 mm -12,5% x S / +20% x S

R = ± 2 mm ≤ DN 200

B = ± 7 mm

S > 4 mm - 12,5% x S / +15% x S  
 ± 3 mm DN 250 - 300