


**COMANDI**

- Telecomando incluso

## CONSOLE

UNITÀ INTERNA		MV-P09BI	MV-P12BI	MV-P18BI
Alimentazione		220-240 / 50Hz / 1phase		
Capacità Raffrescamento	kW	2,7 (0,7 - 3,4)	3,5 (0,8 - 4,4)	5,2 (1,3 - 6,6)
Capacità Riscaldamento	kW	2,9 (0,6 - 3,5)	3,8 (1,1 - 4,4)	5,3 (1,1 - 6,8)
Deumidificazione	l/h	0,8	1,2	1,8
Livello potenza sonora	dB(A)	50/48/42/34	52/50/46/35	57/55/51/42
Livello pressione sonora (Max. ~ Min.)	dB(A)	40/36/32/23	42/40/36/25	47/45/40/31
Portata d'aria (Min. ~ Max.)	m³/h	250/500	280/600	320/700
Peso (netto/lordo)	kg	15,5 / 18,5	15,5 / 18,5	15,5 / 18,5
Dimensioni (LxAxP)	mm	700×600×215	700×600×215	700×600×215
Tubazioni Liquido/Gas	mm (inch)	Φ6/Φ9.52 (1/4"/3/8")	Φ6/Φ9.52 (1/4"/3/8")	Φ6/Φ12 (1/4"/1/2")


**COMANDI**

- Telecomando incluso
- Comando a filo XK19 incluso
- Per controllo tramite WiFi necessario acquistare il comando a filo SWC-04

## SOFFITTO/PAVIMENTO

UNITÀ INTERNA		MV-F09BI	MV-F12BI	MV-F18BI	MV-F24BI
Alimentazione		220-240 / 50Hz / 1phase			
Capacità Raffrescamento	kW	2,6	3,5	4,5	7,1
Capacità Riscaldamento	kW	2,7	4,0	5,0	8,0
Deumidificazione	l/h	0,8	1,4	1,8	2,5
Livello potenza sonora	dB(A)	52/49/44/40	52/49/44/40	52/49/44/40	52/49/44/41
Livello pressione sonora (Max. ~ Min.)	dB(A)	38/35/30/26	38/35/30/26	38/35/30/26	38/35/30/26
Portata d'aria (Min. ~ Max.)	m³/h	420 / 700	420 / 700	410 / 680	720 / 950
Peso (netto/lordo)	kg	25/30	25/30	25,5/30,5	33/40
Dimensioni (LxAxP)	mm	235×870×665	235×870×665	235×870×665	1200×665×235
Tubazioni Liquido/Gas	mm (inch)	Φ6/Φ9.52 (1/4"/3/8")	Φ6/Φ12 (1/4"/1/2")	Φ6/Φ12 (1/4"/1/2")	Φ9.52/Φ16 (3/8"/5/8")


**COMANDI**

- Telecomando incluso
- Comando a filo SWC-04 incluso

## CASSETTA A 4 VIE

UNITÀ INTERNA		MV-C12BI2	MV-C18BI2	MV-C24BI2
Alimentazione		220-240 / 50Hz / 1phase		
Capacità Raffrescamento	kW	3,5	5,0	7,0
Capacità Riscaldamento	kW	4,0	5,5	8,0
Livello potenza sonora	dB(A)	57/52/48/44	59/52/48/44	61/57/55/32
Livello pressione sonora (Max. ~ Min.)	dB(A)	41/36/32/28	43/36/32/28	44/43/40/37
Portata d'aria (Min. ~ Max.)	m³/h	350 / 560	350 / 650	800 / 1100
Peso (netto/lordo)	kg	17/22	17/22	29/36
Dimensioni (LxAxP)	mm	570×265×570	570×265×570	840×240×840
Griglia	mm	60×60	60×60	90×90
Tubazioni Liquido/Gas	mm (inch)	Φ6/Φ9.52 (1/4"/3/8")	Φ6/Φ12 (1/4"/1/2")	Φ6/Φ16 (1/4"/5/8")


**COMANDI**

- Telecomando incluso
- Comando a filo SWC-04 incluso

## CANALIZZATA

UNITÀ INTERNA		MV-D09BI2	MV-D12BI2	MV-D18BI2	MV-D24BI2
Alimentazione		220-240 / 50Hz / 1phase			
Capacità Raffrescamento	kW	2,6	3,5	5,0	7,0
Capacità Riscaldamento	kW	2,8	4,0	5,5	8,0
Livello potenza sonora	dB(A)	47/43/40/37	51/49/46/42	51/46/43/40	61/57/55/51
Livello pressione sonora (Max. ~ Min.)	dB(A)	32/28/25/22	36/34/31/27	36/31/28/25	46/42/40/36
Portata d'aria (Min. ~ Max.)	m³/h	260 / 560	300 / 600	420 / 800	900 / 1300
Peso (netto/lordo)	kg	18,5/22,5	19/23	25/30	31/36
Dimensioni (LxAxP)	mm	710×200×450	710×200×450	1010×200×450	1115×260×655
Tubazioni Liquido/Gas	mm (inch)	Φ6/Φ9.52 (1/4"/3/8")	Φ6/Φ9.52 (1/4"/3/8")	Φ6/Φ12 (1/4"/1/2")	Φ6/Φ16 (1/4"/5/8")
Pressione statica esterna nom/min-max	Pa	25/0-50	25/0-50	25/0-50	25/0-75