



Curve long radius R 1.5 d STD - XS

Codice CUSTD - CUXS	DN	DE	c	a	b	e	SP,STD	PESO Teorico STD	SP,XS	PESO Teorico XS
5	1/2"	21.3	76.2	38.1	47.6	15.9	2.77	0.077	3.73	0.10
7	3/4"	26.7	57.2	28.6	42.9	11.1	2.87	0.077	3.91	0.104
10	1"	33.4	76.2	38.1	55.6	22.2	3.38	0.17	4.55	0.25
12	1" 1/4	42.2	95.2	47.6	68.8	25.4	3.56	0.25	4.85	0.35
15	1" 1/2	48.3	114.3	57.2	82.6	28.6	3.68	0.40	5.08	0.50
20	2"	60.3	152.4	76.2	106.4	34.9	3.91	0.70	5.54	0.95
25	2" 1/2	73.0	190.5	95.2	131.8	44.4	5.16	1.35	7.01	1.80
30	3"	88.9	228.6	114.3	158.8	50.8	5.49	2.20	7.62	2.90
40	4"	114.3	304.8	152.4	209.6	63.5	6.02	4.10	8.56	5.50
50	5"	141.3	381.0	190.5	261.9	79.4	6.55	6.70	9.52	9.40
60	6"	168.3	457.2	228.6	312.7	95.2	7.11	11.00	10.97	16.00
80	8"	219.1	609.6	304.8	414.3	127.0	8.18	21.50	12.70	32.00
100	10"	273.0	762.0	381.0	517.5	158.8	9.27	39.50	12.70	51.00
120	12"	323.8	914.4	457.2	619.1	190.5	9.52	56.50	12.70	73.50
140	14"	355.6	1066.8	533.4	711.2	222.2	9.52	72.00	12.70	92.00
160	16"	406.4	1219.2	609.6	812.8	254.0	9.52	94.50	12.70	122.00
180	18"	457.2	1371.6	685.8	914.4	285.8	9.52	119.00	12.70	157.00
200	20"	508.0	1524.0	762.0	1016.0	317.5	9.52	147.00	12.70	194.00
220	22"	558.8	1676.4	838.2	1117.6	342.9	9.52	178.00	12.70	236.00
240	24"	609.6	1828.8	914.4	1219.2	381.0	9.52	212.00	12.70	282.00